



Platform Lift CURVE EN81-40 compliant  
 Right hand (as viewed from lower level)  
 Platform Size: 1210x830mm  
 Platform 225kg Loading capacity  
 Powder coated in standard RAL 9006  
 Mounting: stanchions  
 2x handheld remotes  
 Outside installation  
 Platform folding support

Production approval:  
 I hereby order the lift system as shown on the drawing and confirm that the layout of the railway is correct. All natural measurements are based on facts given from you. Ascendor is not responsible for charges which are a result from wrong stated measurements.

\_\_\_\_\_  
 date, sign

Stanchions 80x60mm made by Direct Lifts Australia

A = 850mm  
 B = 1200mm  
 C-F = 1450mm (4 pcs.)

230V power supply line (cable 3x1.5mm<sup>2</sup>) to the desired mounting point of the battery charger must be supplied on site. Additional earth connection (min. 6mm<sup>2</sup>) required. Furthermore, fuse protection with a maximum of 13A and an earth-leakage circuit breaker with a tripping fault current of 0.03A must be provided.

Adequate staircase lighting which is independent of a timer must be provided by the customer. A minimum light intensity of 50 lux must be available.

The operator guarantees that there are no supply lines (underfloor heating, electricity, gas, water pipes, etc.) in the area of the stanchions or wall fixings.

Shearing and crushing points that are closer than 100mm to non-contact protected moving parts of the system must be fully covered on site.

A full-surface rail covering in accordance with the applicable building regulations must be provided by the customer.

The user should carry a fully functional mobile phone with him/her on each journey.

Dateityp: ASSEM		Dateiname der Zeichnung: PLK8-HORNSBY	
Allgemeintol. DIN ISO 2768-m-H		Kanten DIN ISO 13715	
Datum 27.07.2020		Name Mayrhofer	
Bear.		Gepr.	
Gepr.		Norm	
Zust.		Änderung	
Datum		Nam. (Urspr.)	
Benennung:		Zeichnungsnummer:	
Blatt1		1 Bl.	
(Ers.f.):		(Ers.d.):	